




DECLARATION OF PERFORMANCE
No. 528001

1. Unique identification code of the product-type: **Xealpro**
2. Intended use/es:
Sealant for façade, exterior and interior, in Cold Climate (type: F EXT-INT CC 25 LM)
Sealant for glazing in Cold Climate (Type: G EXT-INT CC 25 LM)
Sealant for sanitary joints (type: S XS1)
Sealant for pedestrian walkways, exterior and interior, in Cold Climate (type: PW EXT-INT CC 12.5E)
3. Manufacturer: **Novatech International NV**
Industrielaan 5b
2250 Olen - Belgium
4. System/s of AVCP: **3 plus 3**
5. Harmonized standard:
EN 15651-1: 2012-12
EN 15651-2: 2012-12
EN 15651-3: 2012-12
EN 15651-4: 2012-12
6. Notified body: **NB 01213 SKZ-TeConA GmbH**





7. Declared Performance(s)

Conditioning: Method A

Substrate: aluminum (no primer), glass (no primer), and concrete M1 (with primer G783)

| Essential Characteristics | Performance | Harmonized Technical Specification |
|--|-------------|--|
| Reaction to fire | Class E | EN 15651-1: 2012-12 EN 15651-2: 2012-12 EN 15651-3: 2012-12 EN 15651-4: 2012-12 |
| Release of chemicals dangerous to the environment and health | See SDS | |
| Water tightness and air tightness | | |
| Resistance to flow | ≤ 2mm | |
| Loss of volume | ≤ 10% | |
| Elastic recovery | ≥ 70% | |
| Adhesion and cohesion properties after exposure to artificial light | NF | |
| Tensile properties at maintained extension after water immersion | ≤ 0.9MPa | |
| Tensile properties at maintained extension | NF | |
| Tensile properties at maintained extension at -30°C | NF | |
| Tensile properties (secant modulus / elongation at break) | ≤ 0.4 MPa | |
| Tensile properties (secant modulus) at -30°C | ≤ 0.9MPa | |
| Adhesion/cohesion properties at maintained extension after water immersion | NF | |
| Adhesion/cohesion properties at maintained extension after saltwater immersion | NF | |
| Microbiological growth | 0 | |
| Tear resistance | ≤ 12 mm | |
| Durability | Pass | |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Dr. Gunther Dreezen

Director of R&D
 Olen, 20 August 2021

